



Comp 2 Plus SX

Full ester synthetic ultra low smoke 2-stroke engine oil for competition off road motorcycles

Comp 2 Plus SX is a fully synthetic competition 2-stroke oil formulated for modern, high performance, competition air and water cooled engines, especially those with power valve systems. Ideal for motocross engines, Comp 2 Plus SX is also suitable for road going sports 2-strokes.

- High film strength offers maximum performance retention
- Excellent anti-wear characteristics prolong engine life
- Very low ash additive system promoted clean burning
- Ultra low smoke for better environmental acceptance

Comp 2 Plus SX is a clean burning formula that ensures freedom and premix use. When used as a premix, it is recommended for use between 33 and 50 to 1 (3% to 2%) but users are advised to follow engine manufacturers' recommendations. Comp 2 Plus SX should not be mixed with other oils. Comp 2 Plus SX meets or exceeds the requirements of JASO FC and ISO-L-EGD and is compatible with all leaded and unleaded fuel.

Comp 2 Plus SX also meets or exceeds the requirements of JASO FA, JASO FB and API TC.



Typical Technical Data	COMP 2 PLUS SX
Kinematic Viscosity @ 100°C...mm ² /s	12.54
Kinematic Viscosity @ 40°C... mm ² /s	83.02
Viscosity Index	149
Cold Crank Viscosity at -20°C...cp	<3500
SAE Number	10W-30
Pourpoint...°C	-47
Flash Point, Closed Cup...°C	84
API 2-Cycle Performance Spec.	TC
JASO Rating	FC
SG @ 20°C	0.879
ISO Specification	ISO-L-EGD

The above information is supplied to the best of our knowledge and belief on the basis of the current state-of-the-art and our own development work. Subject to amendment.

The information contained herein is believed to be correct at the time of publication. No warranty, expressed or implied, is given concerning the accuracy of the information or suitability of the products. Fuchs Silkolene reserves the right to modify and change its products and specifications without prior notice. Full Material Safety Data Sheets are